

Please rate this document after reviewing at the bottom of this page.

SERVICE DATA

Front Suspension

Item		Specification
Suspension type		Macpherson multi link
Shock absorber	Type	HPD (High Performance Damper)
		ECS(Electronic Control Suspension)

Rear Suspension

Item		Specification
Suspension type		Multi link
Shock absorber	Type	HPD (High Performance Damper)
		ECS(Electronic Control Suspension)

Wheel & Tire

Item		Specification	
		Front	Rear
Aluminum		7.0J * 17	
		8.0J * 18	
		8.0J * 19	8.5J * 19
Tire		225/55 R17	
		225/50 R17	
		225/45 R18	
		225/40 ZR19	225/35 ZR19
Tire pressure kPa (psi)	225/50 R17	250 (36)	
	225/45 R18	250 (36)	270 (39)
	225/40 ZR19	250 (36)	-
	255/35 ZR19	-	For All : 250 (36) For Australia : 260 (38)
	T135/80 R18	420 (60)	

Wheel Alignment

Nomar

Item		Specification		
		Front (2WD)	Front (AWD)	Rear
Toe-in	Total	0.2°±0.2°	0.2°±0.2°	0.4°±0.2°
	Individual	0.1°±0.1°	0.1°±0.1°	0.2°±0.1°
Camber angle		-0.5°±0.5°	-0.5°±0.5°	Wheel&Tire 17, 18 in : -1.5°±0.5°

			Wheel&Tire -1.2 10.0 English
Caster angle	7.00°±0.5°	6.9°±0.5°	-
King-pin angle	14.32°	14.18°	-
Ride height	382±10mm (15.0394 ± 0.3937 in.)	387±10mm (15.2362 ± 0.3937 in.)	380±10mm (14.9606 ± 0.3937 in.)

High Suspension

Item		Specification		
		Front (2WD)	Front (AWD)	Rear
Toe-in	Total	0.2°±0.2°	0.2°±0.2°	0.4°±0.2°
	Individual	0.1°±0.1°	0.1°±0.1°	0.2°±0.1°
Camber angle		-0.15°±0.5°	-0.15°±0.5°	-0.12°±0.5°
Caster angle		6.63°±0.5°	6.55°±0.5°	-
King-pin angle		13.70°	13.53°	-
Ride height		402±10mm (15.8268 ± 0.3937 in.)	407±10mm (16.0236 ± 0.3937 in.)	400±10mm (15.7480 ± 0.3937 in.)

* Thanks for your cooperation for the more quality. Please surely rate this document before closing.