



## Specifications

### Smart Key Unit

Items	Specification
Rated voltage	DC 12 V
Operating voltage	DC 9 - 16 V
Operating temperature	-40 - 176°F (-40 - 80°C)
Load	Max. 4mA (When welcome light function "OFF")

### RF Receiver

Items	Specification
Frequency	433.92 Mhz
Antenna type	FSK (Frequency Shift Keying)

### Smart Key Fob

Items	Specification
Battery	Lithium battery 3V 1EA
Distance	<ul style="list-style-type: none"> <li>- The distance over which RF(Radio Frequency) Receiver can receive a FOB transmission signal : 30m</li> <li>- The distance over which LF(Low Frequency) antenna(Outer Handle/ Trunk/ Liftgate) can detect FOB : 0.7m</li> </ul>
Battery life	<p>More than 2 years (10 times / a day)</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <b>⚠ WARNING</b> <ul style="list-style-type: none"> <li>• An inappropriately disposed battery can be harmful to the environment and human health.</li> <li>• Dispose the battery according to your local law(s) or regulation.</li> </ul> </div>
Push buttons	3 (Door lock / unlock, Liftgate)
Frequency(Rx)	125 kHz
Frequency(Tx)	433.92 MHz
Numbers	2EA

### Antenna

Items	Specification
Rated voltage	DC 12 V
Operating voltage	DC 9 - 16 V
Operating temperature	-22 - 167°F (-30 - 75°C)
Frequency	125kHz
Numbers	Interior (3EA), Door (2EA), Bumper (1EA)